


Product Data Sheet

MaxiCut® Ultra™ 44-3745

Colour – Coating	Black
Colour – Liner	Blue
Design	Palm coated knitwrist
Coating	NBR (Nitrile Butadiene Rubber)
Coating texture	Micro-Foam
Liner	UHMWPE-Glass-Nylon, Spandex
Palm thickness	1.00 mm



Dimensions

Size Range	Size 6 (XS)	Size 7 (S)	Size 8 (M)	Size 9 (L)	Size 10 (XL)	Size 11 (XXL)	Size 12 (XXXL)
Total glove length (+/-10 mm)	200	210	220	230	240	245	250
Wrist length (mm)	60	65	70	70	75	80	85
Wrist width (mm)	65	72	74	76	78	80	82
Palm width (+/-3 mm)	82	86	96	98	100	103	106
Over lock colour	Blue	Red	Orange	White	Yellow	Black	Green

EN test Results

Test	Notified Body	Result/Pass
EN 420: 2003 + A1: 2009	TÜV Rheinland	Yes
EN 388: 2016	TÜV Rheinland	4542C

If a glove due to its design and construction falls outside the scope of EN 420 in terms of hand size dimensions then this glove is classified as "fit for special purpose".



Product Data Sheet

MaxiCut® Ultra™ 44-3745

Typical Performance Values

EN 388:2016 A. Abrasion Resistance	> 8000 Cycles
EN 388:2016 B. Cut Resistance	> 20.0 index
EN 388:2016 C. Tear Resistance	> 75 newtons
EN 388:2016 D. Puncture Resistance	> 60 newtons
EN 388:2016 E. Cut Resistance ISO	≥ 10 Newton

HandCare®

Skin Health Alliance Dermatologically Accredited	Yes
REACH compliant	Yes
Oeko-Tex® 100	Certified
Sanitized®	Yes



Special features

Silicone free	Yes
---------------	-----

Packaging

Pairs per poly bag	12
Poly bags per carton	6
Carton count	72
Carton dimensions (mm)	500 x 295 x 200



Product Data Sheet

MaxiCut® Ultra™ 44-3745

Weight

Size Range	Size 6 (XS)	Size 7 (S)	Size 8 (M)	Size 9 (L)	Size 10 (XL)	Size 11 (XXL)	Size 12 (XXXL)
Glove weight / Pair (+/- 6 gram)	40	46	50	54	58	62	64
Gross Weight (Kg)	4	4.5	3.75	5	5.5	5.65	5.8
Carton Weight (Kg)	1	1	1	1	1	1	1
Net Weight (Kg)	3	3.5	2.75	4	4.5	4.65	4.8

Issue date: 09.08.2018

